

Material Safety Data Sheet

APPEARANCE MATERIALS, INC.
P.O.BOX 116
WESTBROOK, CT. 06498

HMIS HAZARD RATING

0= Insignificant 1= Slight 2= Moderate 3= High 4= Extreme

HEALTH	1	FLAMMABILITY	0	REACTIVITY	0	SPECIFIC HAZ.	G
--------	---	--------------	---	------------	---	---------------	---

Manufacturer
Appearance Materials, Inc., Westbrook Industrial Park
Westbrook, Ct. 06498

Product Formulation Name

C-20 CAR WASH SOAP

EMERGENCY PHONE: 800-582-8343

SECTION 1 – HAZARDOUS INGREDIENTS

INGREDIENTS	CAS NUMBER	OSHA PEL	PERCENT
Dobecylbenzene Sulfonic Acid	27176-87-0	unknown	less than 20%
Ethanolamine	141-43-5	3 ppm	less than 5%

SECTION 11 – PHYSICAL DATA

Boiling Point212 deg. F
Specific Gravity1.01
Vapor PressureUnknown
Melting PointUnknown
Vapor Density (AIR=1)N/A
Evaporation Rate (Butyl Acetate-1)Unknown
Solubility in WaterSoluble in all proportions
Appearance & OdorPink viscous liquid with fruity scent

SECTION 111 – FIRE AND EXPLOSION HAZARD DATA

Flash Point (Text Method)N/A
Flammable Limits (LEL)N/A
Flammable Limits (UEL)N/A
Extinguishing MediaWater, foam, CO2 or dry chemical
Special Fire Fighting ProceduresUse protective clothing, eye protection, and self-contained breathing apparatus.
Unusual Fire and Explosion HazardsNone known

SECTION IV – REACTIVITY DATA

Chemical StabilityStable
Conditions to AvoidNone
Hazardous PolymerizationWill not occur
Hazardous Decomposition ProductsNone
Materials to AvoidNone

SECTION V – HEALTH HAZARD DATA

Routes of EntryInhalation, Skin, Ingestion
Health HazardsIngestion may cause chemical burns of mouth, throat, esophagus and stomach. Prolonged exposure may cause mild irritation to skin, eyes, and nose.
CarcinogenicityNone
Medical ConditionsGenerally aggravated by exposure. Product may aggravate an existing dermatitis.

SECTION VI – FIRST AID MEASURES

Eye ContactFlush with clear water.
Skin ContactWash off with warm water and soap.
InhalationRemove from exposure.
IngestionSeek prompt medical attention.

SECTION VII – PRECAUTIONS FOR SAFE HANDLING & USE

Steps To Be Taken In Case Material Is SpilledAbsorb with dry absorbent, collect for waste disposal, wash away residue with lots of water.
Waste Disposal MethodProduct is biodegradable. Haul to approved class 1 dump.
Precautions To Be Taken in Handling & StoringSpilled material is slippery on walkways and foams profusely when hit with a stream of water.

SECTION VIII – CONTROL MEASURES

Protective GlovesPVC or Butyl Rubber Gloves
Eye ProtectionMonogoggles

The information on this data sheet represents our current data and best opinions as to the proper use and handling of this product under normal conditions. Any use of the product which is not in conformance with this data sheet or which involves using the product in combination with any other product or any process is the responsibility of the user. To the best of our knowledge, this Material Data Sheet conforms to the requirements of US OSHA 29 CFR 1910.1200.

Issue Date: 2/1/14