



Material Safety Data Sheet

HMIS Ratings
 Health 2
 Flammability 2
 Reactivity 0
 Protection X

1 Chemical Product and Company Identification

Manufacturer Information Car Brite, Inc.
 1910 South State Avenue
 Indianapolis, IN 46203

Phone (317) 788-9925

Emergency Phone CHEMTREC
 1-800-424-9300
 FOR INTERNATIONAL
 CALLS
 703-527-3887

Date Prepared 2002-Jul-26

Supersedes 2002-Jun-24

Product Identity FAST WAX

Product Code Number A036

Product Use Automotive Reconditioning Products

Version # 1.1

CAS # Mixture

2 Composition / Information on Ingredients

Ingredient Name	CAS Number	Wgt. %	PEL-OSHA	Exposure Limits		Carcinogen
				TLV-ACGIH		
MINERAL SPIRITS	8052-41-3	10 - 30	100 ppm TWA; 525 mg/m3 TWA	100 ppm TWA		No
KEROSINE, PETROLEUM	8008-20-6	10 - 30				No
KAOLIN	66402-68-4	3 - 7				No
2-PROPANOL	67-63-0	1 - 5	400 ppm TWA; 980 mg/m3 TWA	400 ppm TWA		No
Non-hazardous and other ingredients below reportable levels	Proprietary	52	N/AP	N/AP		N/AP

3 Hazards Identification

Potential Health Effects

Skin Prolonged and/or repeated skin contact with this product may cause irritation/dermatitis.

Eyes This product may cause irritation to the eyes.

Inhalation This product may cause irritation to the respiratory system.

Ingestion Ingestion of this product may cause nausea, vomiting and diarrhea.

Hazard Statements
 COMBUSTIBLE

4 First Aid Measures

First Aid

Skin	For skin contact, wash immediately with soap and water. Immediately take off all contaminated clothing. If irritation persists, get medical attention.
Eyes	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention or advice.
Inhalation	Move person to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen. Seek medical attention.
Ingestion	If the material is swallowed, get immediate medical attention or advice -- Do not induce vomiting.
Notes to Physician	This material, if aspirated into the lungs, may cause chemical pneumonitis; treat the affected person appropriately.

5 Fire Fighting Measures

Hazardous Combustion Products

Carbon monoxide, carbon dioxide and other hydrocarbon fragments.

Extinguishing Media

Carbon dioxide. Alcohol foam.

General Fire Hazards

This product is combustible at high temperatures. Vapors are heavier than air and may travel along the ground to some distant source of ignition and flash back.

Fire Fighting Equipment/Instructions

Firefighters should wear full protective gear.

Flash Point	101 F lowest flashing component	TCC
Flammability Limits in Air, Lower, % by Volume	0.7 %	
Flammability Limits in Air, Upper, % by Volume	6 %	

6 Accidental Release Measures

Containment Procedures

Eliminate sources of ignition. Absorb with inert absorbent such as dry clay, sand or diatomaceous earth, commercial sorbents, or recover using pumps.

Clean-Up Procedures

Absorb spill with inert material. Shovel material into appropriate container for disposal.

7 Handling and Storage

Handling Procedures

Keep this product from heat, sparks, or open flame. Avoid prolonged or repeated skin contact with this material.

Storage Procedures

Keep the container tightly closed. Do not store, incinerate, or heat this material above 120 degrees Fahrenheit. Do not freeze.

8 Exposure Controls / Personal Protection

Engineering Controls

Explosion proof exhaust ventilation should be used.

Personal Protective Equipment

Eyes/Face

Wear chemical goggles.

Skin

Use impervious gloves. Use of impervious apron and boots are recommended.

Respiratory

If ventilation is not sufficient to effectively prevent buildup of vapor/mist/fume/dust, appropriate NIOSH/MSHA respiratory protection must be provided.

General

Eye wash fountain and emergency showers are recommended. Use good industrial hygiene practices in handling this material.

9 Physical & Chemical Properties

Boiling Point	> 212 F
Specific Gravity	< 1
Vapor Pressure	< 20 mm/Hg
Evaporation Rate	Faster than water
Vapor Density	> 1
Solubility (H₂O)	Insoluble
pH	8.5
Freezing Point	32 F

10 Chemical Stability & Reactivity Information

Chemical Stability

This is a stable material.

Hazardous Decomposition

Hazardous combustion products may include carbon monoxide, carbon dioxide and hydrocarbon fragments.

Hazardous Polymerization

Will not occur.

Incompatibility

Strong oxidizing agents (peroxides, chlorine, strong acids).

11 Toxicological Information

Toxicological Information

No data available for this product.

12 Ecological Information

Ecological Information

No data available for this product.

13 Disposal Considerations

Disposal Instructions

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

14 Transportation Information

General

This product is not regulated as a hazardous material by the United States (DOT) or Canadian (TDG) transportation regulations.

15 Regulatory Information

US Federal Regulations

CERCLA/SARA - Section 313 - Emission Reporting

2-PROPANOL

KAOLIN

16 Other Information

Disclaimer

NOTICE: The information presented herein is based on data considered to be accurate as of the date of preparation of this Material Safety Data Sheet. However, MSDS may not be used as a commercial specification sheet of manufacturer or seller, and no warranty or representation, expressed or implied, is made as to the accuracy or comprehensiveness of the foregoing data and safety information, nor is any authorization given or implied to practice any patented invention without a license. In addition, no responsibility can be assumed by vendor for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices, or from any hazards inherent in the nature of the product.

Prepared By Technical Department

Issue Date 26-Jul-2002



Material Safety Data Sheet

HMIS Ratings
 Health 2
 Flammability 0
 Reactivity 0
 Protection X

1 Chemical Product and Company Identification

Manufacturer Information Car Brite, Inc.
 1910 South State Avenue
 Indianapolis, IN 46203

Phone (317) 788-9925

Emergency Phone CHEMTREC
 1-800-424-9300
 FOR INTERNATIONAL
 CALLS
 703-527-3887

Date Prepared 2002-Jul-26

Supercedes 2002-Jun-26

Product Identity BRITE SPOT

Product Code Number E050

Product Use Automotive Reconditioning Product

Version # 1.1

CAS # Mixture

2 Composition / Information on Ingredients

Ingredient Name	CAS Number	Wgt. %	Exposure Limits		Carcinogen
			PEL-OSHA	TLV-ACGIH	
AMIDES, COCO, N-[3-(DIMETHYLAMINO)PROPYL], ALKYLATION PRODUC	70851-07-9	3 - 7	Not Established	Not Established	No
DIPHOSPHORIC ACID, TETRAPOTASSIUM SALT	7320-34-5	1 - 5	Not Regulated	Not Regulated	No
Non-hazardous and other ingredients below reportable levels	Proprietary	92	N/AP	N/AP	N/AP

3 Hazards Identification

Potential Health Effects

Skin Prolonged and/or repeated skin contact with this product may cause irritation/dermatitis.

Eyes This product may cause irritation to the eyes.

Inhalation This product may cause irritation to the respiratory system.

Ingestion Ingestion of this product may cause nausea, vomiting and diarrhea.

Hazard Statements

CAUTION: EYE AND SKIN IRRITANT.

4 First Aid Measures

First Aid

Skin	Immediately take off all contaminated clothing. For skin contact, flush with large amounts of water. If irritation persists, get medical attention.
Eyes	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention or advice.
Inhalation	Move person to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen. Seek medical attention.
Ingestion	If the material is swallowed, get immediate medical attention or advice -- Give several glasses of water or milk.

5 Fire Fighting Measures

Hazardous Combustion Products

Carbon monoxide, carbon dioxide and other hydrocarbon fragments.

Extinguishing Media

Use methods for the surrounding fire.

General Fire Hazards

Not a fire hazard.

Fire Fighting Equipment/Instructions

Firefighters should wear full protective gear.

Flash Point	N/AP
Flammability Limits in Air, Lower, % by Volume	N/AP
Flammability Limits in Air, Upper, % by Volume	N/AP

6 Accidental Release Measures

Containment Procedures

Stop the flow of material, if this is without risk. Dike the spilled material, where this is possible.

Clean-Up Procedures

Absorb spill with inert material. Shovel material into appropriate container for disposal.

7 Handling and Storage

Handling Procedures

Avoid prolonged or repeated skin contact with this material.

Storage Procedures

Keep the container tightly closed. Do not store, incinerate, or heat this material above 120 degrees Fahrenheit. Do not freeze.

8 Exposure Controls / Personal Protection

Engineering Controls

Use local exhaust ventilation.

Personal Protective Equipment

Eyes/Face

Wear chemical goggles.

Skin

Use impervious gloves. Use of impervious boots is recommended.

Respiratory

If ventilation is not sufficient to effectively prevent buildup of aerosols or mists, appropriate NIOSH/MSHA respiratory protection must be provided.

General

Use good industrial hygiene practices in handling this material.

9 Physical & Chemical Properties

Boiling Point	212 F
Specific Gravity	1.04
Vapor Pressure	< 20
Evaporation Rate	Slower than water
Vapor Density	< 1
Solubility (H ₂ O)	Soluble
pH	10
Freezing Point	32 F

10 Chemical Stability & Reactivity Information

Chemical Stability

This is a stable material.

Hazardous Decomposition

Hazardous combustion products may include carbon monoxide, carbon dioxide and hydrocarbon fragments.

Hazardous Polymerization

Will not occur.

Incompatibility

This product may react with strong acids. This product may react with strong alkalies.

11 Toxicological Information

Toxicological Information

No data available for this product.

12 Ecological Information

Ecological Information

No data available for this product.

13 Disposal Considerations

Disposal Instructions

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

14 Transportation Information

General

This product is not regulated as a hazardous material by the United States (DOT) or Canadian (TDG) transportation regulations.

15 Regulatory Information

US Federal Regulations

16 Other Information

Disclaimer

NOTICE: The information presented herein is based on data considered to be accurate as of the date of preparation of this Material Safety Data Sheet. However, MSDS may not be used as a commercial specification sheet of manufacturer or seller, and no warranty or representation, expressed or implied, is made as to the accuracy or comprehensiveness of the foregoing data and safety information, nor is any authorization given or implied to practice any patented invention without a license. In addition, no responsibility can be assumed by vendor for any damage or injury resulting from abnormal use, from any failure to adhere to recommended practices, or from any hazards inherent in the nature of the product.

Prepared By Technical Department
Issue Date 26-Jul-2002



Material Safety Data Sheet

HMIS Ratings
 Health 2
 Flammability 2
 Reactivity 0
 Protection

1 Chemical Product and Company Identification

Manufacturer Information Car Brite, Inc.
 1910 South State Avenue
 Indianapolis, IN 46203

Phone (317) 788-9925

Emergency Phone CHEMTREC
 1-800-424-9300
 FOR INTERNATIONAL
 CALLS
 703-527-3887

Date Prepared 2004-Jan-06

Supersedes 2003-Nov-26

Product Identity SEE SPOT GO

Product Code Number E019

Product Use Automotive Reconditioning Products

Version # 1.0

CAS # Mixture

2 Composition / Information on Ingredients

Ingredient Name	CAS Number	Wgt. %	PEL-OSHA	Exposure Limits		Carcinogen
				TLV-ACGIH		
PROPANE	74-98-6	48 - 55	1000 ppm TWA; 1800 mg/m3 TWA	2500 ppm TWA		No
BUTANE	106-97-8	45 - 49	800 ppm TWA; 1900 mg/m3 TWA	800 ppm TWA		No
ETHANOL, 2-BUTOXY-	111-76-2	10 - 20	25 ppm TWA; 120 mg/m3 TWA	20 ppm TWA		No
LIQUIFIED PETROLEUM GAS MIXTURE	Mixture	1 - 10	not established	not established		No

3 Hazards Identification

Potential Health Effects

Skin Prolonged or repeated contact with this product may dry and/or defat the skin.

Eyes This product may be severely irritating to the eyes. Symptoms include itching, burning, redness and tearing.

Inhalation This product may cause irritation to the respiratory system. Excessive inhalation of this product may cause headache, dizziness, blurred vision, nausea and vomiting.

Potential Health Effects

Ingestion Ingestion of large amounts may produce gastrointestinal disturbances including irritation, nausea, and diarrhea. Small amounts of this product, if aspirated into the lungs, may cause mild to severe pulmonary injury.

Hazard Statements

CONTENTS UNDER PRESSURE.

4 First Aid Measures

First Aid

Skin For skin contact, wash immediately with soap and water. If irritation persists, get medical attention.

Eyes Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention or advice.

Inhalation Move person to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen.

Ingestion If the material is swallowed, get immediate medical attention or advice -- Do not induce vomiting.

5 Fire Fighting Measures

Hazardous Combustion Products

Carbon monoxide, carbon dioxide and other hydrocarbon fragments.

Extinguishing Media

Alcohol foam. Carbon dioxide. Dry chemical.

General Fire Hazards

Pressurized Container: May explode when exposed to heat or flame.

Fire Fighting Equipment/Instructions

Firefighters should wear full protective gear.

Flash Point	< 0 F (propellant)
Flammability Limits in Air, Lower, % by Volume	1.9 % (propellant)
Flammability Limits in Air, Upper, % by Volume	9.5 % (propellant)

6 Accidental Release Measures

Clean-Up Procedures

Absorb spill with inert material. Shovel material into appropriate container for disposal.

7 Handling and Storage

Handling Procedures

Keep this product from heat, sparks, or open flame.

Storage Procedures

Do not store, incinerate, or heat this material above 120 degrees Fahrenheit (48°C). Do not freeze.

8 Exposure Controls / Personal Protection

Engineering Controls

Explosion proof exhaust ventilation should be used.

Personal Protective Equipment

Eyes/Face

Wear chemical goggles.

Skin

Use impervious gloves. Use of impervious apron and boots are recommended.

Respiratory

If ventilation is not sufficient to effectively prevent buildup of aerosols or mists, appropriate NIOSH/MSHA respiratory protection must be provided.

General

Use good industrial hygiene practices in handling this material.

9 Physical & Chemical Properties

Specific Gravity	0.931
Vapor Pressure	71 psig @70F
Solubility (H2O)	SLIGHT
pH	11.84

10 Chemical Stability & Reactivity Information

Chemical Stability

This is a stable material.

Hazardous Decomposition

Hazardous combustion products may include carbon monoxide, carbon dioxide and hydrocarbon fragments.

Hazardous Polymerization

Will not occur.

Incompatibility

None known.

11 Toxicological Information

Toxicological Information

No data available for this product.

12 Ecological Information

Ecological Information

No data available for this product.

13 Disposal Considerations

Disposal Instructions

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

14 Transportation Information

US DOT HMR Information

Proper Shipping Name	Consumer commodity
Identification Number	None
Hazard Class	ORM-D
Labels Required	None

15 Regulatory Information

16 Other Information

Prepared By	Technical Department
Issue Date	06-Jan-2004



Material Safety Data Sheet

HMIS Ratings
 Health 1
 Flammability 4
 Reactivity 0
 Protection X

1 Chemical Product and Company Identification

Manufacturer Information Car Brite, Inc.
 1910 South State Avenue
 Indianapolis, IN 46203

Phone (317) 788-9925

Emergency Phone CHEMTREC
 1-800-424-9300
 FOR INTERNATIONAL
 CALLS
 703-527-3887

Date Prepared 2003-Jan-09

Supersedes 2001-Oct-12

Product Identity XTRA DUTY (AEROSOL)

Product Code Number E006

Product Use Automotive Reconditioning Products

CAS # Mixture

2 Composition / Information on Ingredients

Ingredient Name	CAS Number	Wgt. %	PEL-OSHA	Exposure Limits		Carcinogen
				TLV-ACGIH		
LIQUIFIED PETROLEUM GAS MIXTURE	Mixture	5 - 10	not established	not established		No
ETHANOL, 2-BUTOXY-	111-76-2	1 - 5	25 ppm TWA; 120 mg/m3 TWA	20 ppm TWA		No
Non-hazardous and other ingredients below reportable levels	Proprietary	89.5	N/AP	N/AP		N/AP

3 Hazards Identification

Potential Health Effects

Skin Prolonged or repeated contact with this product may dry and/or defat the skin.

Eyes This product may be severely irritating to the eyes. Symptoms include itching, burning, redness and tearing.

Inhalation This product may cause irritation to the respiratory system. Excessive inhalation of this product may cause headache, dizziness, blurred vision, nausea and vomiting.

Ingestion Ingestion of large amounts may produce gastrointestinal disturbances including irritation, nausea, and diarrhea. Small amounts of this product, if aspirated into the lungs, may cause mild to severe pulmonary injury.

Hazard Statements

CONTENTS UNDER PRESSURE.

4 First Aid Measures

First Aid

Skin	For skin contact, wash immediately with soap and water. If irritation persists, get medical attention.
Eyes	Immediately flush eyes with plenty of water for at least 15 minutes. Get medical attention or advice.
Inhalation	Move person to fresh air. If not breathing, give artificial respiration, preferably mouth-to-mouth. If breathing is difficult, give oxygen.
Ingestion	If the material is swallowed, get immediate medical attention or advice -- Do not induce vomiting.

5 Fire Fighting Measures

Hazardous Combustion Products

Carbon monoxide, carbon dioxide and other hydrocarbon fragments.

Extinguishing Media

Alcohol foam. Carbon dioxide. Dry chemical.

General Fire Hazards

Pressurized Container: May explode when exposed to heat or flame.

Fire Fighting Equipment/Instructions

Firefighters should wear full protective gear.

Flash Point	< 0 F (propellant)
Flammability Limits in Air, Lower, % by Volume	1.9 % (propellant)
Flammability Limits in Air, Upper, % by Volume	9.5 % (propellant)

6 Accidental Release Measures

Clean-Up Procedures

Absorb spill with inert material. Shovel material into appropriate container for disposal.

7 Handling and Storage

Handling Procedures

Keep this product from heat, sparks, or open flame.

Storage Procedures

Do not store, incinerate, or heat this material above 120 degrees Fahrenheit. Do not freeze.

8 Exposure Controls / Personal Protection

Engineering Controls

Explosion proof exhaust ventilation should be used.

Personal Protective Equipment

Eyes/Face

Wear chemical goggles.

Skin

Use impervious gloves.

Respiratory

If ventilation is not sufficient to effectively prevent buildup of aerosols or mists, appropriate NIOSH/MSHA respiratory protection must be provided.

General

Use good industrial hygiene practices in handling this material.

9 Physical & Chemical Properties

Specific Gravity < 1

Vapor Pressure 60 psig

pH 10.49

10 Chemical Stability & Reactivity Information

Chemical Stability

This is a stable material.

Hazardous Decomposition

Hazardous combustion products may include carbon monoxide, carbon dioxide and hydrocarbon fragments.

Hazardous Polymerization

Will not occur.

Incompatibility

None known.

11 Toxicological Information

Toxicological Information

No data available for this product.

12 Ecological Information

Ecological Information

No data available for this product.

13 Disposal Considerations

Disposal Instructions

Dispose of waste material according to Local, State, Federal, and Provincial Environmental Regulations.

14 Transportation Information

US DOT HMR Information

Proper Shipping Name	Consumer commodity
Identification Number	None
Hazard Class	ORM-D
Labels Required	None

15 Regulatory Information

16 Other Information

Prepared By	Technical Department
Issue Date	09-Jan-2003