

Material Safety Data Sheet

APPEARANCE MATERIALS, INC.
P.O.BOX 116
WESTBROOK, CT. 06498

HMIS HAZARD RATING

0= Insignificant 1= Slight 2= Moderate 3= High 4= Extreme

HEALTH	2	FLAMMABILITY	2	REACTIVITY	1	SPECIFIC HAZ.	G
---------------	----------	---------------------	----------	-------------------	----------	----------------------	----------

Manufacturer

Appearance Materials, Inc., Westbrook Industrial Park
Westbrook, Ct. 06498

Product Formulation Name

D-92 ULTRA GLOSS 2

EMERGENCY PHONE: 800-582-8343

SECTION 1 – HAZARDOUS INGREDIENTS

INGREDIENTS	CAS NUMBER	WEIGHT	Supplier OEL
Distillates, petroleum, hydrotreated light	64742-47-8	75%	300 ppm 1900 mg/m3

SECTION 11 – PHYSICAL DATA

Boiling Point	420 deg. F
Specific Gravity	0.940 gm/ml
Vapor Pressure	0.05 MM Hg @ 20 deg. C
Melting Point	-94 deg. F
Solubility in Water	Negligible, less than 0.1%
Appearance & Odor	Blue water thin liquid with strawberry odor

SECTION 111 – FIRE AND EXPLOSION HAZARD DATA

Flash Point (Text Method)	174 deg. F
Flammable Limits (LEL)	0.6%
Flammable Limits (UEL)	7%
Extinguishing Media	Foam, water spray, dry chemical, CO2
Special Fire Fighting Procedures	Wear self-contained breathing apparatus and protective suit.
Unusual Fire and Explosion Hazards	Keep containers and surroundings cool with water spray.

SECTION IV – REACTIVITY DATA

Chemical Stability	Stable
Conditions to Avoid	Keep away from heat and sources of ignition
Hazardous Polymerization	None
Hazardous Decomposition Products	Hazardous gases and vapors produced in fire are oxides of carbon.
Materials to Avoid	Avoid contact with strong oxidants

SECTION V – HEALTH HAZARD DATA

Routes of Entry	Inhalation, Skin, Ingestion
Health Hazards	High vapor concentrations are irritating to the eyes and the respiratory tract, and may cause headaches and dizziness, are anesthetic. May have other central nervous system effects, including death.
Carcinogenicity	None
Signs & Symptoms of Exposure	Liquid may irritate eyes. Vapor may cause irritation of eyes and respiratory tract. May cause headaches and dizziness.
Medical Conditions	Generally aggravated by exposure. May aggravate an existing dermatitis.

SECTION VI – FIRST AID MEASURES

Eye Contact	Flush with clear water.
Skin Contact	Wash off with warm water and soap.
Inhalation	Remove from exposure and call physician immediately.
Ingestion	Drink large amounts of water. Do not induce vomiting.

SECTION VII – PRECAUTIONS FOR SAFE HANDLING & USE

Steps To Be Taken In Case Material Is Spilled	Keep people away. Eliminate all ignition sources. Ventilate area. Absorb spilled material with earth, sand, or other suitable absorbent. Minimize skin contact.
Waste Disposal Method	In accordance with federal, state, or local regulations.
Precautions To Be Taken in Handling & Storing	Use only with ventilation sufficient to prevent exceeding exposure limit or buildup of explosive concentrations of vapor in air. No smoking, open lights, or other sources of heat or ignition.

SECTION VIII – CONTROL MEASURES

Local Exhaust Ventilation	Recommended in use areas
Protective Gloves	PVC or Butyl Rubber Gloves
Eye Protection	Monogoggles

The information on this data sheet represents our current data and best opinions as to the proper use and handling of this product under normal conditions. Any use of the product which is not in conformance with this data sheet or which involves using the product in combination with any other product or any process is the responsibility of the user. To the best of our knowledge, this Material Data Sheet conforms to the requirements of US OSHA 29 CFR 1910.1200.

Issue Date: 3/10/11