

KAR KRAFT SYSTEMS, LLC 20 PRIVILEGE ST. WOONSOCKET, RI 02895
TEL. NO. (401) 769-6100
MATERIAL SAFETY DATA SHEET DATE PRINTED:6/29/2015

HP-95 SUPREME DRESSING
DOT: NAERG-2000 Guide # - 171

Hazardous Ingredients CAS Number/List	OSHA PEL ppm	ACGIH TLV ppm	%
=====			
=No reportable ingredients.			

Physical/Chemical Characteristics
=====

=Milky liquid. Water soluble.
Specific Gravity = 1.0

Fire Hazard Data
=====

=Flash Point not applicable. Water-based solution, does not burn.

Reactivity Data
=====

=Stable. No hazardous decomposition products. Will not polymerize.

Health Hazard Data
=====

=Routes of entry: Skin and ingestion.
Health Hazards: (acute) Irritant. Eye irritant. can be irritating to skin, eyes, and gastrointestinal system.

Not listed as OSHA, NTP or IARC carcinogen.

Symptoms of exposure: Eye irritation.
Condition aggravated by exposure: Dermatitis

Emergency and First Aid Procedures: Flush eyes with water for 15 minutes and get medical attention immediately. If swallowed, drink 2 glasses of water and call a physician at once.

Precautions for Safe Handling and Use
=====

=For Spills: Rinse spill area with clear water.

Waste Disposal: No special disposal provisions.

Precautions for Handling and Storing: Keep from freezing. Wear protective equipment for eyes. Prevent splashing.

Page #2

HP-95 SUPREME PLUS SILICONE EMULSION

Control Measures

=====

=Respiratory Protection: Not applicable

Ventilation: No special provisions.

Protective Gloves: Wear waterproof gloves as needed.

Eye Protection: Wear splash-proof goggles.

Other Equipment: As needed.

Work Practices: Avoid getting material in eyes. wear protective equipment. Wash any exposed skin with water to reduce chance of irritation. Wash hands after use.

EPA Supplier Notification

=====

=This mixture contains no chemicals subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 and 40 CFR Part 372. None of the ingredients are on the List of Extremely Hazardous Substances for SARA Emergency Planning, Tier I/Tier II Hazard Category (40 CFR 370): Immediate Health Hazard (irritant).

Updated: 8/02
January, 1995

Page #3
AS-31-S
ACRYLIC SOLVENT

Control Measures

=====
=Respiratory Protection: In confined spaces, use organic vapor respirator.
=Ventilation: Use adequate ventilation, or open doors to increase ventilation.
=Protective Gloves: Wear solvent-proof gloves.
=Eye Protection: Wear splash-proof goggles.
=Work Practices: Avoid getting material on skin or in eyes. Avoid inhaling mist or vapor. Wash hands after use and before eating or smoking. Wear protective equipment. Wash any exposed skin with water. Remove any wet clothing. Do not smoke near or while using this material.

EPA Supplier Notification

=====
=This mixture contains the following chemicals subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR Part 372: Toluene, Xylene (mixed isomers), Ethyl Benzene. None of the ingredients are included on the List of Extremely Hazardous Substances for SARA Emergency Planning, Tier I/ Tier II Hazard Categories (40 CFR 370) for this material: Fire hazard and Immediate Health Hazard.

Updated: 8/02
August, 1990

Page #3
AS-31-S
ACRYLIC SOLVENT

Control Measures

=====
=Respiratory Protection: In confined spaces, use organic vapor respirator.
=Ventilation: Use adequate ventilation, or open doors to increase ventilation.
=Protective Gloves: Wear solvent-proof gloves.
=Eye Protection: Wear splash-proof goggles.
=Work Practices: Avoid getting material on skin or in eyes. Avoid inhaling mist or vapor. Wash hands after use and before eating or smoking. Wear protective equipment. Wash any exposed skin with water. Remove any wet clothing. Do not smoke near or while using this material.

EPA Supplier Notification

=====
=This mixture contains the following chemicals subject to the reporting requirements of section 313 of Title III of the Superfund Amendments and Reauthorization Act of 1986 (SARA) and 40 CFR Part 372: Toluene, Xylene (mixed isomers), Ethyl Benzene. None of the ingredients are included on the List of Extremely Hazardous Substances for SARA Emergency Planning. Tier I/ Tier II Hazard Categories (40 CFR 370) for this material: Fire hazard and Immediate Health Hazard.

Updated: 8/02
August, 1990

KAR KRAFT SYSTEMS, LLC 20 PRIVILEGE ST. WOONSOCKET, RI 02895
 TEL. NO. (401) 769-6100
 MATERIAL SAFETY DATA SHEET DATE PRINTED:6/29/2015

AS-31-S ADHESIVE REMOVER
 DOT: NAERG-2000 Guide # - 128

Hazardous Ingredients CAS Number/List	OSHA PEL ppm	ACGIH TLV ppm	%
Special Naphtholite 66/3 64742-48-9	300	300	
Toluene 108-88-3 (SARA 313)	100	100	>23
Xylene (Mixed Isomers) 1330-20-7 (SARA 313)	100	100	>24
Ethyl Benzene 100-41-4 (SARA 313)	100	100	>3
Low Odor Based Solvent Petroleum Distillates 64742-47-8	300	300	>35

Physical/Chemical Characteristics

=Clear, volatile liquid. Naphtha odor. Insoluble in water.
 Specific Gravity = 0.831.

Fire Hazard Data

=Flash Point 45°F. Flammable. Use dry chemical, foam or CO₂
 extinguisher.

Reactivity Data

=Stable. Will not polymerize. Combustion products: CO, CO₂. Keep
 away from strong acids, strong bases, oxidizing agents, and
 amines.